

YZHH Series Automatic Double Pre-fold Folder Gluer

This machine is specially used for paperboard shaping and adhesive processing after cutting horizontally. Its universality is strong and suitable scope is wide, which can fold and paste various straight seaming box.


It is widely used in food, medicine, cosmetics, stationery and other ordinary cartons. Pre-fold section is applied to auto packaging, fold 1 and fold 3 of all cartons can reach 180° and 135°, perfectly combining the requirements of auto packaging together.

Table of Contents

- Characteristics
- Technical Parameter
- Related

Model	YZHH-600, YZHH-800
Paper Material	200-800 gsm cardboard and E, F corrugated paper.
Max. Liner speed	220m/min
Feeding Way	Automatically and continuously feeding.
Way of Folding in reverse	Fold 1 and fold 3 are 180 degree and 135 degree. Fold 2 and fold 4 are 180 degree.
Glue Material	Water-base cold glue.
Electric Power	3P 380V 50Hz
Main Power	5.5kW
Weight	2T, 2.2T
Over Dimension	10.5×1.1×1.4m, 10.5×1.3×1.4m

Technical Parameter



Common Box Type and Size				
Model	YZHH-600		YZHH-800	
Paper Material	Cardboard	E/F Corrugated Paper	Cardboard	E/F Corrugated Paper
A	70-700mm	150-580mm	70-700mm	150-580mm
B	120-580mm	180-480mm	120-780mm	180-680mm
C	Min.: 10mm	Min.: 15mm	Min.: 10mm	Min.: 15mm
D	Min.: 50mm	Min.: 120mm	Min.: 50mm	Min.: 120mm
F	Min.: 50mm	Min.: 50mm	Min.: 50mm	Min.: 50mm